

## 100W Auto Power Inverter with Dual USB (2100mA)

Model: HEEC-210-AC110 / AC230



### SPECIFICATIONS

- **MODEL TYPE: AC110 & AC230**
- DC Input: 12V / 15A
- AC Output: (100W continuous)
  - **AC110 Model:** 100~125V, 60Hz
  - **AC230 Model:** 200~250V, 50Hz
  - Output Waveform: Modified Sine Wave
- USB Output (2 Ports): 5V DC / 2100mA
- LED status indicator :
  - Green : Normal Operation
  - Red : Fault Condition
- Fuse Protection: 15A internal fuse
- Optimum Efficiency: 88%
- Low Voltage Shutdown: Input Voltage  $<10.8 \pm 0.6$  V
- Operating Temperature: 3 ~ 40 °C ( 37 ~ 104 °F)
- Storage Temperature: 0 ~ 50 °C ( 32 ~ 122 °F)
- Compact Design with the retractable cigarette plug
- Product Dimension: 80 x 50 x 44 mm (not including plug)

### OPERATING INSTRUCTIONS

- Pull out cigarette plug slowly until hearing a click sound.
- Plug into cigarette lighter socket or directly connect to 12V DC source.
- The power LED indicator lights green when the inverter is properly connected to a functioning DC power source. The AC and USB outlets are ready to use.
- Plug equipment into the AC receptacle of the inverter; turn the equipment on
- Plug USB compatible device into USB outlets; the device will be charging automatically

**WARNING:** To avoid continuously consuming vehicle batteries' electricity, unplug the inverter from 12V DC power source when engine shots off.